

CHEM-EXTENDER Thickening Agent

913 Rue Michelin, Laval, Québec, Canada, H7L 5B6 www.epoxychemtec.com

## Product Description:

CHEM-EXTENDER is a fluffed and dried synthetic polyethylene pulp. It is non-hazardous, resists mildew and biological growth and can be used in a wide variety of applications including adhesives, textured, cement, or industrial coatings and sealants. It is used in various applications to improve their dimensional stability, strength, and crack resistances.

## Technical Data:

Packaging:	1 KG
Color:	White fluffy fibers
Odor:	No significant odor
Melting Point:	125 – 135 °C
Specific gravity:	0.96 g/cm <sup>3</sup>
Shelf Life:	2 years in unopened containers
VOC:	0 g/L

## Caution:

Fiber dust should be considered a nuisance. Avoid breathing dust and control dust accumulations. Avoid the use of air jets if possible to prevent fibers from becoming airborne. Wash hands and skin thoroughly after handling. Consult the material safety data sheet for further information.

\*Consult the safety data sheet for further information.\*

## Important Notice:

All statements, recommendations and technical information contained in this document are accurate to the best knowledge of Chemtec. The data relates only to the specific material designated herein. It may not be valid if used in combination with any other materials. It is the users' responsibility to verify suitability of this information for their own particular use, and to test this product before use. Chemtec assumes no legal responsibility for use upon these data. Chemtec assumes no legal responsibility for any direct, indirect, consequential, economic, or any other damage except to replace the product or refund the purchase price as set out in the purchase agreement.