
Product Description:

Xylene is a narrow boiling range, medium evaporating solvent widely used in the paint and chemical industry. This solvent is recommended as a cleaner for all of our epoxy and polyurethane coatings.

Technical Data:

Packaging:	3.78L (1 US gallon) or 18.9L (5 US gallon)
Physical state/ Color:	Liquid/clear
Odor:	Aromatic
Flash Point (closed cup):	>23 °C (73°F)
Specific gravity:	0.87 g/cm ³
Flammability:	Highly flammable liquid and vapor
Shelf Life:	12 months in unopened containers

Caution:

Highly flammable liquid and vapor! Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe mist/vapors. Wash hands and skin thoroughly with soap and water after handling. Consult the material safety data sheet for further information.

Consult the safety data sheet for further information.

Important Notice:

All statements, recommendations and technical information contained in this document are accurate to the best knowledge of Chemtec. The data relates only to the specific material designated herein. It may not be valid if used in combination with any other materials. It is the users' responsibility to verify suitability of this information for their own particular use, and to test this product before use. Chemtec assumes no legal responsibility for use upon these data. Chemtec assumes no legal responsibility for any direct, indirect, consequential, economic, or any other damage except to replace the product or refund the purchase price as set out in the purchase agreement.